


LED 12V^(DC)

Netzgeräte 12 Vdc
power supplies 12 Vdc




SELV    

prim. input	sec. output	Gehäuse housing	Abmessungen dimensions	Gewicht weight	Kabel cable	Umgebungs- temperatur ta	Artikel- nummer ref.-No.
230 Vac 50 - 60 Hz	12 Vdc 5,4W / 0,45A	Kunststoff plastic	58x64x18mm	40 g	sec. 1200 mm 5,5 Koax	max. 40°C	550-058-01



SELV    

prim. input	sec. output	Gehäuse housing	Abmessungen dimensions	Gewicht weight	Kabel cable	Umgebungs- temperatur ta	Artikel- nummer ref.-No.
230 Vac 50 - 60 Hz	12 Vdc 4,2W / 0,35A	Kunststoff plastic	37x26x22mm	36 g	prim. 150 mm sec. 150 mm 	max. 50°C	550-087-50



SELV    

prim. input	sec. output	Gehäuse housing	Abmessungen dimensions	Gewicht weight	Kabel cable	Umgebungs- temperatur ta	Artikel- nummer ref.-No.
100 - 240 Vac 50 - 60 Hz	12 Vdc 24W / 2,0A	Kunststoff plastic	77x80 x33mm	164 g	sec. 1800 mm 5,5 Koax	max. 40°C	550-057-51