

# LED power 700

Netzgeräte mit Überlastschutz und Kurzschlußschutz

Power supplies with overload protection and short-circuit-protection



CE IP<sub>44</sub> SELV OO



prim. input	sec. output	Gehäuse housing	Abmessungen dimensions	Gewicht weight	Kabel prim./sec. cable prim./sec.	Umgebungs- temperatur ta	Artikel- nummer ref.-No.
195-260Vdc / 50 - 60 Hz	700 mA konstant 1 LED (3W)	Kunststoff plastic	52x26x22mm	40g	80mm	max. 50°C	556-040-50



CE IP<sub>20</sub> SELV OO



prim. input	sec. output	Gehäuse housing	Abmessungen dimensions	Gewicht weight	Kabel sec. cable sec.	Umgebungs- temperatur ta	Artikel- nummer ref.-No.
95-260Vdc / 50 - 60 Hz	700 mA konstant 1-3 LED (3W)	Kunststoff plastic	101x42x20mm	50g	150mm	max. 50°C	556-024-50

dimmbar mit Potentiometer 50 Ohm

dimmable with potentiometer 50 Ohm 550-099-50



CE IP<sub>20</sub> SELV KEMA 05



prim. input	sec. output	Gehäuse housing	Abmessungen dimensions	Gewicht weight	Kabel cable	Umgebungs- temperatur ta	Artikel- nummer ref.-No.
220-240Vdc / 50 - 60 Hz	700 mA Konstant 1 - 6 LED 3 W	Kunststoff plastic	128x38x28mm	90g	ohne without	max. 50°C	556-047-50



CE IP<sub>20</sub> SELV



prim. input	sec. output	Gehäuse housing	Abmessungen dimensions	Gewicht weight	Kabel cable	Umgebungs- temperatur ta	Artikel- nummer ref.-No.
220-240Vdc / 50 - 60 Hz	700 mA Konstant 1 - 5 LED 3 W	Kunststoff plastic	123x38x21mm	80g	ohne without	-15°C - 40°C	556-061-50